

TEXAS DEPARTMENT OF INSURANCE

Engineering Services Program / MC 103-3A, 333 Guadalupe Street, P.O. Box 149104, Austin, Texas 78714-9104
Phone No. (512) 322-2212 Fax No. (512) 463-6693

PRODUCT EVALUATION

DR-523

Effective Date March 1, 2012

Reevaluation Date: **October 2013**

The following product has been evaluated for compliance with the wind loads specified in the **International Residential Code (IRC)** and the **International Building Code (IBC)**.

This product evaluation is not an endorsement of this product or a recommendation that this product be used. The Texas Department of Insurance has not authorized the use of any information contained in the product evaluation for advertising, or other commercial or promotional purpose.

This product evaluation is intended for use by those individuals who are following the design wind load criteria in Chapter 3 of the IRC and Section 1609 of the IBC. The design loads determined for the building or structure shall not exceed the design load rating specified for the products shown in the limitations section of this product evaluation. This product evaluation does not relieve a Texas licensed engineer of his responsibilities as outlined in the Texas Insurance Code, the Texas Administrative Code, and the Texas Engineering Practice Act.

Ultra Aluminum Clad Wood Gardenaire Sliding Doors, Non-Impact Resistant, manufactured by

Kolbe & Kolbe Millwork Co., Inc.
1323 South Eleventh Avenue
Wausau, WI 54401
(715) 842 - 5666

General Description:

System	Description	Label Rating	Design Pressure Rating	Hallmark Certification
1	Ultra Gardenaire Sliding Door – Wide Stiles	LC-PG45 96x98 – SD SD-LC45 96x98	+45/-45	413-H-1070.00 413-H-1070.01

Product Dimensions:

System	Overall Size	Panel Size
1	96" x 98 $\frac{7}{16}$ "	Two: 48 $\frac{1}{4}$ " x 95 $\frac{5}{8}$ "

Hardware:

- Polished brass pull handle; One (1) required; Located 40 inches from bottom rail of active panel.
- Single point lock with strike plate; One (1) required; Located 40 inches from the bottom of the rail and adjacent vertical frame.
- Adjustable metal rollers; Two (2) required; Located 6 $\frac{1}{2}$ inches from each stile of the operable panel bottom.

Product Identification (Certification Agency Label on Door):

System	Certification Agency	WDMA
1	Manufacturer's Name or Code Name	Kolbe & Kolbe Millwork Co., Inc.
	Product Name	Ultra Gardenaire Sliding Door – Wide Stiles
	Test Standards	AAMA/WDMA/CSA 101/I.S.2/A440-05 AAMA/WDMA/CSA 101/I.S.2/A440-08

Impact Resistance:

Impact Resistant	Requirement
No	Impact protective system required when product is installed in areas where windborne debris protection is required

INSTALLATION INSTRUCTIONS

Installation:

Option 1: The door assembly shall be fastened to minimum Southern Yellow Pine lumber. The door assembly is secured to the wall framing using Kolbe & Kolbe metal installation clips. The installation clips (1 $\frac{5}{8}$ " x 10 $\frac{1}{16}$ " x 0.04") are secured to the door frame side jambs, head, and sill. The clips are secured to the door frame with two (2) No. 8 x $\frac{3}{4}$ " screws. The clips are secured to the wall framing with one (1) No. 8 x 1 $\frac{3}{4}$ " screw. The fasteners shall be long enough to penetrate a minimum of 1 $\frac{1}{2}$ inches into the wall framing. The spacing of the clips is specified in the table below.

Installation Clip Spacing:

System	Distance From Each Corner	Head (on center spacing)	Sill (on center spacing)	Side Jambs (on center spacing)
1	Head/Sill: 16" Side Jambs: 14 $\frac{1}{16}$ "	16"	16"	14 $\frac{1}{16}$ "

Option 2: The door assembly shall be fastened to minimum Southern Yellow Pine lumber. The door assembly is secured to the wall framing using the door frame with minimum No. 10 x 3" screws. The fasteners shall be long enough to penetrate a minimum of 1 $\frac{1}{2}$ inches into the wall framing. The spacing of the fasteners is specified in the table below.

Fastener Spacing:

System	Distance From Each Corner	Head (on center spacing)	Sill (on center spacing)	Side Jambs (on center spacing)
1	Head/Sill: 4" Side Jambs: 9 $\frac{7}{16}$ "	11"	11"	9 $\frac{7}{16}$ "

Nailing Flange (Options 1 and 2): The vinyl nailing flange is secured to the wall framing with minimum 12 smooth shank gauge roofing nails spaced 10 inches on center along the head and side jambs.

Note: The manufacturer's installation instructions shall be available on the job site during installation. All fasteners shall be corrosion resistant as specified in the International Residential Code (IRC), the International Building Code (IBC), and the Texas Revisions.